

Package: Thermistor (via r-universe)

September 3, 2024

Type Package

Title The Simulation of the Thermistor Network

Version 1.1.0

Description Given the circuit topology, simulating the Voltage vs. Temperature curve with a set of Resistors (R1, R2, R3 and R4) and Thermistors values (TH1 and TH2) for a given thermistor network shown in Seth DeLand (2024) ``Optimal Component Selection Using the Mixed-Integer Genetic Algorithm" <https://ww2.mathworks.cn/matlabcentral/fileexchange/35810-optimal-component-selection-using-the-mixed-integer-genetic-algorithm> and the application in Mak and Wu (2019) [doi:10.1080/00401706.2019.1593246](https://doi.org/10.1080/00401706.2019.1593246).

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.2.1

Imports ggplot2

Depends R (>= 2.10)

Author Yao Xiao [aut, cre] (<https://orcid.org/0000-0002-2826-1347>),
Kang Fu [aut] (<https://orcid.org/0000-0002-0398-2340>)

Maintainer Yao Xiao <xystatistics@mails.cnu.edu.cn>

NeedsCompilation no

Date/Publication 2024-04-05 15:43:02 UTC

Repository <https://zuelxy.r-universe.dev>

RemoteUrl <https://github.com/cran/Thermistor>

RemoteRef HEAD

RemoteSha 9789d731496735e2afbc01f1cfc731211cd5e1a8

Contents

CompValues	2
plot_voltageCurve	2
SquaredLoss	3
tempCompCurve	4
voltageCurve	5

Index	6
--------------	----------

CompValues	<i>Dataset for the standard components values</i>
------------	---

Description

A list containing the standard values provided for each component. "Res" corresponds to the values of R1, R2, R3 and R4, The values in the same index of "ThBeta" and "ThVal" provides nine types of (beta, Rb) of a thermistor.

Usage

```
data(CompValues)
```

Format

A named list containing the standard values of each component:

"Res" the standard values of R1, R2, R3 and R4

"ThBeta" the standard values of temperature coefficient

"ThVal" the standard values of nominal thermistor resistances

Examples

```
data(EzGP_data)
```

plot_voltageCurve	<i>Plot the V-DeltaT Curve</i>
-------------------	--------------------------------

Description

Plot the temperature-change-voltage curve under a particular components setting v.s. the target curve. using ggplot.

Usage

```
plot_voltageCurve(Tdata, OnlyTarget = TRUE, Pdata = NULL)
```

Arguments

Tdata a vector of temperature-change values
 OnlyTarget logical. If TRUE, plot the target curve only.
 Pdata the values returning by voltageCurve or tempCompCurve

Value

the graph

Examples

```
### only target curve
Tdata <- seq(-40, 85, by = 5)
plot_voltageCurve(Tdata)
### a particular curve and the target curve
data(CompValues)
Tdata <- seq(-40, 85, by=5)
R_id <- c(43, 36, 29, 15, 9, 3)
Res <- CompValues$Res
ThVal <- CompValues$ThVal
ThBeta <- CompValues$ThBeta
Vnew <- voltageCurve(Tdata, R_id, Res, ThVal, ThBeta)
plot_voltageCurve(Tdata, OnlyTarget = FALSE, Pdata = Vnew)
```

SquaredLoss

Squared Loss of Objective

Description

Measuring the difference between the V-DeltaT Curve you get and the target curve under squared loss.

Usage

SquaredLoss(x, StdRes, StdTherm_Val, StdTherm_Beta, Tdata)

Arguments

x a vector of the indices of each component
 StdRes a vector of available resistor values
 StdTherm_Val a vector of available nominal thermistor resistances
 StdTherm_Beta a vector of of thermistor temperature coefficients
 Tdata a vector of temperature-change values

Value

the squared loss

Examples

```

data(CompValues)
Tdata <- seq(-40, 85, by=5)
R_id <- c(43, 36, 29, 15, 9, 3)
Res <- CompValues$Res
ThVal <- CompValues$ThVal
ThBeta <- CompValues$ThBeta
SquaredLoss(R_id, Res, ThVal, ThBeta, Tdata)
### 0.04066336

```

tempCompCurve

Calculate V-DeltaT Curve

Description

Calculating the temperature-change-voltage curve for a particular set of Resistor and Thermistor Values.

Usage

```
tempCompCurve(x, Tdata)
```

Arguments

x a vector containing the values of R1 R2 R3 R4 Rb1 Beta1 Rb2 Beta2
Tdata a vector of temperature-change values

Value

the voltage values at Point B

Examples

```

Tdata <- seq(-40, 85, by=5)
R_values <- c(1100, 4300, 560, 1100, 220, 3680, 1000, 3560)
tempCompCurve(x = R_values, Tdata = Tdata)

```

voltageCurve	<i>Calculate V-DeltaT Curve for Given Indices</i>
--------------	---

Description

Calculating the temperature-change-voltage curve for a particular set of indices for each component corresponding to the values from a standard components space.

Usage

```
voltageCurve(Tdata, x, StdRes, StdTherm_Val, StdTherm_Beta)
```

Arguments

Tdata	a vector of temperature-change values
x	a vector of the indices of each component
StdRes	a vector of available resistor values
StdTherm_Val	a vector of available nominal thermistor resistances
StdTherm_Beta	a vector of of thermistor temperature coefficients

Value

the voltage values at Point B

Examples

```
data(CompValues)
Tdata <- seq(-40, 85, by=5)
R_id <- c(2, 1, 4, 2, 1, 3)
Res <- CompValues$Res
ThVal <- CompValues$ThVal
ThBeta <- CompValues$ThBeta
voltageCurve(Tdata, R_id, Res, ThVal, ThBeta)
```

Index

* **dataset**

CompValues, [2](#)

CompValues, [2](#)

plot_voltageCurve, [2](#)

SquaredLoss, [3](#)

tempCompCurve, [4](#)

voltageCurve, [5](#)